

BioChela Dissolve

Biological degreaser for smooth and porous surfaces.

BioChela Dissolve is quick acting and effective in removing petroleum based oils and greases. BioChela Dissolve, inoculates oil and grease based stains with micro-organisms which works to degrade the contamination. Essential micronutrients stimulate this action. In this way, BioChela will remove stains imbedded in porous concrete, stone, asphalt and soil as well as non-porous surfaces.

Benefits

- Removes stains ordinary products cannot
- Keeps working on imbedded stains
- Deals with surface stains
- Biodegradable
- Enhances biodegradation above and below ground surface
- Cleans oily plant equipment, vehicles and tools
- Solvent free
- Micronutrients boost activity

Directions for Use

Dilutions

Heavy stains	1 litre BioChela Dissolve to 2 litres water
Light stains	1 litre BioChela Dissolve to 4 litres water
Pressure washing	1 litre BioChela Dissolve to 1 litre water

Porous Surfaces (concrete, pavers, masonry and asphalt)

Remove surface oils with CareClean E. Rinse and spray on BioChela Dissolve solution. Allow it to work for 20 to 30 minutes. Keep damp by applying more solution as necessary and agitate with a brush. After 30 minutes lightly rinse with clean water.

Any imbedded stain will slowly disappear over some days.



CERT NO FS60515

Chela Ltd is a
BS EN ISO9002:1994
registered organisation

Chela Ltd

78 Bilton Way • Enfield • Middlesex EN3 7LW • UK
Tel +44 (0)20 8805 2150 • Fax +44 (0)20 8443 1868
E-mail mail@chela.co.uk • Website www.chela.co.uk

**Soil**

Scrape surface, dampen and apply BioChela Dissolve solution. Scrape the surface again and lightly spray with water.

Non-porous Surfaces

Wash with CareClean E. Spray or brush on a 1:4 solution of BioChela Dissolve. Leave it to allow the micro-organisms to work.

Do not use in direct sunlight on painted surfaces.

Pressure Washing

Pre-wash using CareClean E. Spray surface with 1:1 dilution of BioChela Dissolve. Pressure rinse from top to bottom up. Keep surfaces wet for as long as possible.

PRECAUTION

Read Material Safety Data Sheet before use. Pre-test new finishes by applying to a small area first. Works best on damp, porous surfaces.



CERT NO FS60515

Chela Ltd is a
BS EN ISO9002:1994
registered organisation